


SEE NO EVIL

VAN DAMME MINIATURE 75 OHM PLASMA GRADE COAX



Van Damme Miniature 75 Ohm Plasma Grade Video Coaxial Cable has been designed to provide the best possible performance from a low overall diameter stranded video cable. The range is mechanically equivalent to RG179 and available in the 6 colours commonly associated with video signals.

KEY BENEFITS



Precision 75Ω
Impedance



Multiple
colours



Flexibility

MATERIALS



Oxygen Free
Copper



Polyethylene



Flexible PVC

APPLICATIONS



Broadcast



Video



Presentations

SEE NO EVIL

Applications

- Analogue video transmission up to 30 metres
- Internal rack and patch panel wiring
- Multipin connector breakouts

Application Notes

- Uses RG179 type crimp connectors
- Colour coding suitable for RGBHV, RGBS, YUV and other video formats

Mechanical Specification

Conductor	7 x 0.12 mm bare ultra-pure oxygen-free copper
Conductor size	7 x 0.12 mm, 0.08 mm ² , AWG 30/7
Dielectric	Foam skin polyethylene
Diameter	1.60 ± 0.05 mm
Screen	16 x 5 x 0.10 mm bare braided oxygen free copper, > 95% coverage
Overall Jacket	Flexible PVC
Overall diameter	2.60 ± 0.15 mm
Bend Radius	15 x overall diameter
Operating temperature	-20 to +70 °C

Electrical Specification

Impedance	75 ± 5 Ohms
Conductor Resistance	235 Ohm/km
Capacitance	56.5 pF/m
Velocity of Propagation	80%
Attenuation (dB/100m)	10 MHz 6.99
	50 MHz 15.77
	100 MHz 22.74
	135 MHz 26.64
	180 MHz 30.99

Part Numbers and Description

Part Number	Description	RAL Code	Max. Reel Length
268-408-000	Van Damme Plasma Grade miniature coax Jet Black	RAL 9005	500 m
268-406-020	Van Damme Plasma Grade miniature coax Flame Red	RAL 3000	500 m
268-403-040	Van Damme Plasma Grade miniature coax Lemon Yellow	RAL 1012	500 m
268-404-050	Van Damme Plasma Grade miniature coax Mint Green	RAL 6029	500 m
268-402-060	Van Damme Plasma Grade miniature coax Sky Blue	RAL 5015	500 m
268-400-090	Van Damme Plasma Grade miniature coax Oyster White	RAL 1013	500 m



SEE NO EVIL

Recommended BNC Connectors

335-012-000	Van Damme BNC cable male RG179B/U
335-014-179	Van Damme BNC cable female RG179B/U
335-012-179	Van Damme BNC bulkhead female RG179B/U Neutrik rearTWIST HD BNC NBTC75BLI4

Connector selection criteria:

Conductor 0.38 mm Dielectric diameter 1.60 mm Overall diameter 2.60 mm (0.38/1.6/2.6)

Standards and Compliance

RoHS 2011/65/EU Restriction of Hazardous Substances

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals